

UTILITY
PATENT APPLICATION
TRANSMITTAL

Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. INK-006

First Named Inventor Albert

Title Color Electrophoretic Displays

APPLICATION ELEMENTS

1. ☒ Fee Transmittal Form
2. ☒ Specification and Drawings
☒ - Specification - (29 pages)
☒ - Claims - (2 pages)
☒ - Abstract - (1 page)
☒ - Sheets of Drawings - (14 sheets)
☐ Formal
☒ Informal
3. ☐ Oath or Declaration [Total Pages 4]
a. ☐ Newly executed (original)
b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 16 completed)
[Note Box 4 below]
4. ☐ Incorporation by Reference (usable if Box 3b is checked)
The entire Disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 3b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
5. ☐ Microfiche Computer Program (Appendix)
6. ☐ Nucleotide and/or Amino Acid Sequence Submission
☐ Computer Readable Copy
☐ Paper Copy (identical to computer copy)
☐ Statement verifying identify of above copies

ADDRESS TO: Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

ACCOMPANYING APPLICATION PARTS

7. ☐ 37 CFR 3.73(b) Statement (when there is an assignee)
☐ Power of Attorney
8. ☐ English Translation Document (if applicable)
9. ☐ Information Disclosure Statement (IDS)/PTO-1449
☐ Copies of IDS Citations
10. ☐ Preliminary Amendment
☐ Drawings [Total Sheets]
☐ Letter to Official Draftsperson Including Drawings [Total Pages]
11. ☒ Return Receipt Postcard
12. ☒ Small Entity Statement(s) (Unsigned)
☐ Statements filed in prior application,
(Status still proper and desired)
13. ☐ Certified Copy of Priority Document(s)
14. ☐ Deletion of Inventor(s)
Signed statement attached deleting inventor(s) named in the prior application.
15. ☒ Patent Application Data Entry Form
16. ☐ Other:

17. ☒ If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:
☐ Continuation ☐ Divisional ☒ Continuation-in-part (CIP) of prior applications listed on attached sheet.
Priority to the above application(s) is claimed under 35 U.S.C. 120.
Prior application information: Examiner: _____ Group/Art Unit: _____

18. ☒ Priority - 35 U.S.C. 119
☒ See attached sheets.
☐ The certified copy has been filed in prior U.S. application Serial No. _____/_____ on _____.
☐ The certified copy will follow.

CORRESPONDENCE ADDRESS


Direct all correspondence to: Patent Administrator
Testa, Hurwitz & Thibault, LLP
High Street Tower
125 High Street
Boston, MA 02110
Tel. No.: (617) 248-7000
Fax No.: (617) 248-7100

SIGNATURE BLOCK

Date: August 27, 1998

Reg. No. 40,060
Tel. No.: (617) 248-7604
Fax No.: (617) 248-7100

Respectfully submitted,


John D. Lanza
Attorney for Applicants
Testa, Hurwitz & Thibault, LLP
High Street Tower
125 High Street
Boston, MA 02110

FEE TRANSMITTAL

Note. Effective October 1, 1997.
Patent fees are subject to annual revision

Complete if Known

Application Serial Number	Not Yet Assigned
Filing Date	Herewith
First Named Inventor	Albert
Group Art Unit	Not Yet Assigned
Examiner Name	Not Yet Assigned
Attorney Docket No.	INK-006

METHOD OF PAYMENT

1. ☒ Payment Enclosed:
☒ Check ☐ Money Order ☐ Other
2. ☐ The Commissioner is hereby authorized to credit or charge any fee indicated below to Deposit Account No. 20-0531.
☐ Required Fees (copy of this sheet enclosed).
☐ Additional fee required under 37 CFR 1.16 and 1.17.
☐ Overpayment Credit.

FEE CALCULATION

1. FILING FEE

Large Entity

Fee (\$)	Fee Description	Fee Paid
790	Utility filing fee	790
330	Design filing fee	
150	Provisional filing fee	

	Number Filed	Number Extra	Rate	Amount
Total Claims	10	- 20 = 0	x \$ 22.00 =	0

Independent Claims	3	- 3 = 0	x \$ 82.00 =	0
--------------------	---	---------	--------------	---

☐ Multiple Dependent Claim(s), if any \$270.00 = 0

TOTAL: 790.00

SMALL ENTITY DISCOUNT: 395.00

SUBTOTAL (1) (\$) 395.00

2. AMENDMENT CLAIM FEES

Claims Remaining After Amend.	Highest No. Previously Paid For	Present Extra	Rate	Fee Paid
-------------------------------	---------------------------------	---------------	------	----------

Total - = x \$ 22.00 =

Indep. - = x \$ 82.00 =

☐ First Presentation of Multiple Dep. Claim + \$270.00 =

TOTAL: (\$)

SMALL ENTITY DISCOUNT: (\$)

SUBTOTAL (2) (\$) 0.00

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity Fee (\$)	Small Entity Fee (\$)	Fee Description	Fee Paid
130	65	Surcharge - late filing fee or oath	
50	25	Surcharge - late provisional filing fee or	
130	130	Non-English specification	
2,520	2,520	For filing a request for reexamination	
110	55	Extension for reply within first month	
400	200	Extension for reply within second month	
950	475	Extension for reply within third month	
1,510	755	Extension for reply within fourth month	
2,060	1,030	Extension for reply within fifth month	
310	155	Notice of Appeal	
310	155	Filing a brief in support of an appeal	
270	135	Request for oral hearing	
130	130	Petitions to the Commissioner	
50	50	Petitions related to provisional applications	
240	240	Submission of Information Disclosure Statement (37 CFR 1.97(c))	
130	130	Submission of Information Disclosure Statement (37 CFR 1.97(d))	
790	395	Filing a submission after final rejection (37 CFR 1.129(a))	
790	395	For each additional invention to be examined (37 CFR 1.129(b))	
		Other (Specify)	

SUBTOTAL (3) (\$) 0.00

SUBTOTAL (1) 395.00

SUBTOTAL (2) 0.00

SUBTOTAL (3) 0.00

TOTAL (\$) 395.00


CORRESPONDENCE ADDRESS

Direct all correspondence to:

Patent Administrator
 Testa, Hurwitz & Thibault, LLP
 High Street Tower
 125 High Street
 Boston, MA 02110
 Tel. No.: (617) 248-7000
 Fax No.: (617) 248-7100

SIGNATURE BLOCK

Date: August 27, 1998
 Reg. No. 40,060
 Tel. No.: (617) 248-7604
 Fax No.: (617) 248-7100

Respectfully submitted,

 John D. Lanza
 Attorney for Applicants
 Testa, Hurwitz & Thibault, LLP
 High Street Tower
 125 High Street
 Boston, MA 02110

**STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(c))-- SMALL BUSINESS CONCERN**

Attorney Docket No. **INK-006**

Applicant, Patentee, or Identifier: **Albert et al.**
Application or Patent No.: **Not Yet Assigned**
Filed or Issued: **Herewith**
Title: **Color Electrophoretic Displays**

I hereby state that I am

- ☐ the owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN: E Ink Corporation.

ADDRESS OF SMALL BUSINESS CONCERN: 45 Spinelli Place, Cambridge, MA 02138.

I hereby state that the above identified small business concern qualifies as a small business concern as defined in 37 CFR 1.9(d) and 13 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time, or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby state that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization having any rights in the invention is listed below:

- ☒ no such person, concern, or organization exists.
☐ each such person, concern, or organization is listed below.

Separate statements are required from each named person, concern or organization having rights to the invention stating their status as small entities. (37 CFR 1.27).

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

NAME OF PERSON SIGNING Russell J. Wilcox

TITLE OF PERSON IF OTHER THAN OWNER Vice President, Business Development

ADDRESS OF PERSON SIGNING 45 Spinelli Place, Cambridge, MA 02138

SIGNATURE _____

DATE _____

INVENTOR INFORMATION

Inventor One Given Name :: Jonathan D.
Family Name :: Albert
Name Suffix ::
Postal Address Line One :: 347 Putnam Avenue
Postal Address Line Two ::
City :: Cambridge
State/Province :: MA
Country :: USA
Postal or Zip Code :: 02139
City of Residence :: Cambridge
State/Prov. of Residence :: MA
Country of Residence :: USA
Citizenship :: USA

Inventor Two Given Name :: Barrett
Family Name :: Comiskey
Name Suffix ::
Postal Address Line One :: 346 Putnam Avenue
Postal Address Line Two ::
City :: Cambridge
State/Province :: MA
Country :: USA
Postal or Zip Code :: 02139
City of Residence :: Cambridge
State/Prov. of Residence :: MA
Country of Residence :: USA
Citizenship :: USA

Inventor Three Given Name :: Joseph M.
Family Name :: Jacobson
Name Suffix ::
Postal Address Line One :: 223 Grant Avenue
Postal Address Line Two ::
City :: Newton Centre
State/Province :: MA
Country :: USA
Postal or Zip Code :: 02159
City of Residence :: Newton Centre
State/Prov. of Residence :: MA
Country of Residence :: USA
Citizenship :: USA

Correspondence Information

Correspondence Customer Number :: 021323

Application Information

Title Line One :: Color Electrophoretic Displays
Title Line Two ::
Total Drawing Sheets :: 14
Formal Drawings ::
Application Type :: Utility
Docket Number :: INK-006
Licensed - U S Government Agency ::
Contract Number ::
Grant Number ::
Secrecy Order in Parent Application ::

Representative Information

Representative Customer Number :: 021323

Continuity Information

This application is a :: Continuation-in-Part of
>Application One :: 08/504,896
Filing Date :: July 20, 1995
Patent Number ::
This application is a :: Continuation-in-Part of
>Application Two :: 08/983,404
Filing Date :: July 19, 1997
Patent Number ::
This application is a :: Continuation-in-Part of
>Application Three :: 08/935,800
Filing Date :: September 23, 1997
Patent Number ::
This application is a :: Claim Benefit of
>Application Four :: 60/057,133
Filing Date :: August 28, 1997
Patent Number ::
This application is a :: Claim Benefit of
>Application Five :: 60/057,716
Filing Date :: August 28, 1997
Patent Number ::
This application is a :: Claim Benefit of
>Application Six :: 60/057,122
Filing Date :: August 28, 1997
Patent Number ::
This application is a :: Claim Benefit of
>Application Seven :: 60/057,798
Filing Date :: August 28, 1997
Patent Number ::

This application is a ::	Claim Benefit of
>Application Eight ::	60/057,799
Filing Date ::	August 28, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Nine ::	60/057,163
Filing Date ::	August 28, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Ten ::	60/057,118
Filing Date ::	August 28, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Eleven ::	60/059,358
Filing Date ::	September 19, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twelve ::	60/059,543
Filing Date ::	September 19, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Thirteen ::	60/065,529
Filing Date ::	November 18, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Fourteen ::	60/065,630
Filing Date ::	November 18, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Fifteen ::	60/065,605
Filing Date ::	November 18, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Sixteen ::	60/066,147
Filing Date ::	November 19, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Seventeen ::	60/066,245
Filing Date ::	November 20, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Eighteen ::	60/066,246
Filing Date ::	November 20, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Nineteen ::	60/066,115
Filing Date ::	November 21, 1997
Patent Number ::	

36230"29804T60

This application is a ::	Claim Benefit of
>Application Twenty ::	60/066,334
Filing Date ::	November 21, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-One ::	60/066,418
Filing Date ::	November 24, 1997
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-Two ::	60/070,940
Filing Date ::	January 9, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-Three ::	60/071,371
Filing Date ::	January 15, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-Four ::	60/072,390
Filing Date ::	January 9, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-Five ::	60/070,939
Filing Date ::	January 9, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-Six ::	60/070,935
Filing Date ::	January 9, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-Seven ::	60/074,454
Filing Date ::	February 12, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-Eight ::	60/076,955
Filing Date ::	March 5, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Twenty-Nine ::	60/076,959
Filing Date ::	March 5, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Thirty ::	60/076,957
Filing Date ::	March 5, 1998
Patent Number ::	
This application is a ::	Claim Benefit of
>Application Thirty-One ::	60/076,978
Filing Date ::	March 5, 1998
Patent Number ::	

PATENT APPLICATION
DOCKET NO.: INK-006
(2108/)

COLOR ELECTROPHORETIC DISPLAYS

Field of the Invention

The present invention relates to electronic displays and, in particular, to color electrophoretic displays.

Cross-Reference to Related Applications

- 5 This application is a continuation-in-part of U.S.S.N. 08/504,896 filed July 20, 1995, U.S.S.N. 08/983,404 filed July 19, 1997, and U.S.S.N. 08/935,800 filed September 23, 1997, the contents of all of which are incorporated herein by reference. This application claims priority to U.S.S.N. 60/057,133 filed August 28, 1997, U.S.S.N. 60/057,716, filed August 28, 1997, U.S.S.N. 60/057,122, filed August 28, 1997, U.S.S.N. 60/057,798, filed August 28, 1997, U.S.S.N. 60/057,799 filed August 28, 1997, U.S.S.N. 60/057,163 filed August 28, 1997, U.S.S.N. 60/057,118, filed August 28, 1997, U.S.S.N. 60/059,358, filed September 19, 1997, U.S.S.N. 60/059,543 filed September 19, 1997, U.S.S.N. 60/065,529, filed November 18, 1997, U.S.S.N. 60/065,630 filed November 18, 1997, U.S.S.N. 60/065,605 filed November 18, 1997, U.S.S.N. 60/066,147, filed 15 November 19, 1997, U.S.S.N. 60/066,245, filed November 20, 1997, U.S.S.N. 60/066,246, filed November 20, 1997, U.S.S.N. 60/066,115 filed November 21, 1997, U.S.S.N. 60/066,334 filed November 21, 1997, U.S.S.N. 60/066,418 filed November 24, 1997, U.S.S.N. 60/070,940 filed January 9, 1998, U.S.S.N. 60/071,371 filed January 15, 1998, U.S.S.N. 60/072,390 filed January 9, 1998, U.S.S.N. 60/070,939 filed January 9, 20 1998, U.S.S.N. 60/070,935 filed January 9, 1998, U.S.S.N. 60/074,454, filed February 12, 1998, U.S.S.N. 60/076,955 filed March 5, 1998, U.S.S.N. 60/076,959 filed March 5, 1998, U.S.S.N. 60/076,957 filed March 5, 1998, U.S.S.N. 60/076,978 filed

00443443506US

March 5, 1998, U.S.S.N. 60/078,363 filed March 18, 1998, U.S.S.N. 60/083,252 filed April 27, 1998, U.S.S.N. 60/085,096 filed May 12, 1998, U.S.S.N. 60/090,223 filed June 22, 1998, U.S.S.N. 60/090,232 filed June 22, 1998, U.S.S.N. 60/092,046 filed July 8, 1998, U.S.S.N. 60/092,050 filed July 8, 1998, and U.S.S.N. 60/093,689 filed July 22, 1998, the contents of all of which are incorporated herein by reference.

Background of the Invention

Traditionally, electronic displays such as liquid crystal displays have been made by sandwiching an optoelectrically active material between two pieces of glass. In many cases each piece of glass has an etched, clear electrode structure formed using indium tin oxide. A first electrode structure controls all the segments of the display that may be addressed, that is, changed from one visual state to another. A second electrode, sometimes called a counter electrode, addresses all display segments as one large electrode, and is generally designed not to overlap any of the rear electrode wire connections that are not desired in the final image. Alternatively, the second electrode is also patterned to control specific segments of the displays. In these displays, unaddressed areas of the display have a defined appearance.

Electrophoretic display media, generally characterized by the movement of particles through an applied electric field, are highly reflective, can be made bistable, and consume very little power. Encapsulated electrophoretic displays also enable the display to be printed. These properties allow encapsulated electrophoretic display media to be used in many applications for which traditional electronic displays are not suitable, such as flexible displays. The electro-optical properties of encapsulated displays allow, and in some cases require, novel schemes or configurations to be used to address the displays.

Summary of the Invention

An object of the invention is to provide a highly-flexible, reflective display which can be manufactured easily, consumes little (or no in the case of bistable displays) power, and can, therefore, be incorporated into a variety of applications. The invention features a

printable display comprising an encapsulated electrophoretic display medium. The resulting display is flexible. Since the display media can be printed, the display itself can be made inexpensively.

An encapsulated electrophoretic display can be constructed so that the optical
5 state of the display is stable for some length of time. When the display has two states which are stable in this manner, the display is said to be bistable. If more than two states of the display are stable, then the display can be said to be multistable. For the purpose of this invention, the term bistable will be used to indicate a display in which any optical state remains fixed once the addressing voltage is removed. The definition of a bistable
10 state depends on the application for the display. A slowly-decaying optical state can be effectively bistable if the optical state is substantially unchanged over the required viewing time. For example, in a display which is updated every few minutes, a display image which is stable for hours or days is effectively bistable for that application. In this invention, the term bistable also indicates a display with an optical state sufficiently long-
15 lived as to be effectively bistable for the application in mind. Alternatively, it is possible to construct encapsulated electrophoretic displays in which the image decays quickly once the addressing voltage to the display is removed (i.e., the display is not bistable or multistable). As will be described, in some applications it is advantageous to use an encapsulated electrophoretic display which is not bistable. Whether or not an
20 encapsulated electrophoretic display is bistable, and its degree of bistability, can be controlled through appropriate chemical modification of the electrophoretic particles, the suspending fluid, the capsule, and binder materials.

An encapsulated electrophoretic display may take many forms. The display may comprise capsules dispersed in a binder. The capsules may be of any size or shape. The
25 capsules may, for example, be spherical and may have diameters in the millimeter range or the micron range, but is preferably from ten to a few hundred microns. The capsules may be formed by an encapsulation technique, as described below. Particles may be encapsulated in the capsules. The particles may be two or more different types of

2025 RELEASE UNDER E.O. 14176

particles. The particles may be colored, luminescent, light-absorbing or transparent, for example. The particles may include neat pigments, dyed (laked) pigments or pigment/polymer composites, for example. The display may further comprise a suspending fluid in which the particles are dispersed.

5 The successful construction of an encapsulated electrophoretic display requires the proper interaction of several different types of materials and processes, such as a polymeric binder and, optionally, a capsule membrane. These materials must be chemically compatible with the electrophoretic particles and fluid, as well as with each other. The capsule materials may engage in useful surface interactions with the
10 electrophoretic particles, or may act as a chemical or physical boundary between the fluid and the binder.

 In some cases, the encapsulation step of the process is not necessary, and the electrophoretic fluid may be directly dispersed or emulsified into the binder (or a precursor to the binder materials) and an effective “polymer-dispersed electrophoretic
15 display” constructed. In such displays, voids created in the binder may be referred to as capsules or microcapsules even though no capsule membrane is present. The binder dispersed electrophoretic display may be of the emulsion or phase separation type.

 Throughout the specification, reference will be made to printing or printed. As used throughout the specification, printing is intended to include all forms of printing and
20 coating, including: premetered coatings such as patch die coating, slot or extrusion coating, slide or cascade coating, and curtain coating; roll coating such as knife over roll coating, forward and reverse roll coating; gravure coating; dip coating; spray coating; meniscus coating; spin coating; brush coating; air knife coating; silk screen printing processes; electrostatic printing processes; thermal printing processes; and other similar
25 techniques. A “printed element” refers to an element formed using any one of the above techniques.

 This invention provides novel methods and apparatus for controlling and addressing particle-based displays. Additionally, the invention discloses applications of

2025022804460

these methods and materials on flexible substrates, which are useful in large-area, low cost, or high-durability applications.

In one aspect, the present invention relates to an encapsulated electrophoretic display. The display includes a substrate and at least one capsule containing a highly-
5 resistive fluid and a plurality of particles. The display also includes at least two electrodes disposed adjacent the capsule, a potential difference between the electrodes causing some of the particles to migrate toward at least one of the two electrodes. This causes the capsule to change optical properties.

In another aspect, the present invention relates to a colored electrophoretic
10 display. The electrophoretic display includes a substrate and at least one capsule containing a highly-resistive fluid and a plurality of particles. The display also includes colored electrodes. Potential differences are applied to the electrodes in order to control the particles and present a colored display to a viewer.

In yet another aspect, the present invention relates to an electrostatically
15 addressable display comprising a substrate, an encapsulated electrophoretic display adjacent the substrate, and an optional dielectric sheet adjacent the electrophoretic display. Application of an electrostatic charge to the dielectric sheet or display material modulates the appearance of the electrophoretic display.

In still another aspect, the present invention relates to an electrostatically
20 addressable encapsulated display comprising a film and a pair of electrodes. The film includes at least one capsule containing an electrophoretic suspension. The pair of electrodes is attached to either side of the film. Application of an electrostatic charge to the film modulates the optical properties.

In still another aspect, the present invention relates to an electrophoretic display
25 that comprises a conductive substrate, and at least one capsule printed on such substrate. Application of an electrostatic charge to the capsule modulates the optical properties of the display.

09140362-032708

In still another aspect the present invention relates to a method for matrix addressing an encapsulated display. The method includes the step of providing three or more electrodes for each display cell and applying a sequence of potentials to the electrodes to control movement of particles within each cell.

5 In yet another aspect, the present invention relates to a matrix addressed electrophoretic display. The display includes a capsule containing charged particles and three or more electrodes disposed adjacent the capsule. A sequence of voltage potentials is applied to the three or more electrodes causing the charged particles to migrate within the capsule responsive to the sequence of voltage potentials.

10 In still another aspect, the present invention relates to a rear electrode structure for electrically addressable displays. The structure includes a substrate, a first electrode disposed on a first side of the substrate, and a conductor disposed on a second side of the substrate. The substrate defines at least one conductive via in electrical communication with both the first electrode and the conductor.

15 Brief Description of the Drawings

 The invention is pointed out with particularity in the appended claims. The advantages of the invention described above, together with further advantages, may be better understood by referring to the following description taken in conjunction with the accompanying drawings. In the drawings, like reference characters generally refer to the
20 same parts throughout the different views. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention.

 FIG. 1A is a diagrammatic side view of an embodiment of a rear-addressing electrode structure for a particle-based display in which the smaller electrode has been
25 placed at a voltage relative to the large electrode causing the particles to migrate to the smaller electrode.

FIG. 1B is a diagrammatic side view of an embodiment of a rear-addressing electrode structure for a particle-based display in which the larger electrode has been placed at a voltage relative to the smaller electrode causing the particles to migrate to the larger electrode.

5 FIG. 1C is a diagrammatic top-down view of one embodiment of a rear-addressing electrode structure.

FIG. 2A is a diagrammatic side view of an embodiment of a rear-addressing electrode structure having a retroreflective layer associated with the larger electrode in which the smaller electrode has been placed at a voltage relative to the large electrode causing the particles to migrate to the smaller electrode.

10

FIG. 2B is a diagrammatic side view of an embodiment of a rear-addressing electrode structure having a retroreflective layer associated with the larger electrode in which the larger electrode has been placed at a voltage relative to the smaller electrode causing the particles to migrate to the larger electrode.

15 FIG. 2C is a diagrammatic side view of an embodiment of a rear-addressing electrode structure having a retroreflective layer disposed below the larger electrode in which the smaller electrode has been placed at a voltage relative to the large electrode causing the particles to migrate to the smaller electrode.

FIG. 2D is a diagrammatic side view of an embodiment of a rear-addressing electrode structure having a retroreflective layer disposed below the larger electrode in which the larger electrode has been placed at a voltage relative to the smaller electrode causing the particles to migrate to the larger electrode.

20

FIG. 3A is a diagrammatic side view of an embodiment of an addressing structure in which a direct-current electric field has been applied to the capsule causing the particles to migrate to the smaller electrode.

25

FIG. 3B is a diagrammatic side view of an embodiment of an addressing structure in which an alternating-current electric field has been applied to the capsule causing the particles to disperse into the capsule.

202302924760

FIG. 3C is a diagrammatic side view of an embodiment of an addressing structure having transparent electrodes, in which a direct-current electric field has been applied to the capsule causing the particles to migrate to the smaller electrode.

FIG. 3D is a diagrammatic side view of an embodiment of an addressing structure having transparent electrodes, in which an alternating-current electric field has been applied to the capsule causing the particles to disperse into the capsule.

FIG. 4A is a diagrammatic side view of an embodiment of a rear-addressing electrode structure for a particle-based display in which multiple smaller electrodes have been placed at a voltage relative to multiple larger electrodes, causing the particles to migrate to the smaller electrodes.

FIG. 4B is a diagrammatic side view of an embodiment of a rear-addressing electrode structure for a particle-based display in which multiple larger electrodes have been placed at a voltage relative to multiple smaller electrodes, causing the particles to migrate to the larger electrodes.

FIG. 5A is a diagrammatic side view of an embodiment of a rear-addressing electrode structure for a particle-based display having colored electrodes and a white electrode, in which the colored electrodes have been placed at a voltage relative to the white electrode causing the particles to migrate to the colored electrodes.

FIG. 5B is a diagrammatic side view of an embodiment of a rear-addressing electrode structure for a particle-based display having colored electrodes and a white electrode, in which the white electrode has been placed at a voltage relative to the colored electrodes causing the particles to migrate to the white electrode.

FIG. 6 is a diagrammatic side view of an embodiment of a color display element having red, green, and blue particles of different electrophoretic mobilities.

FIGS. 7A-7B depict the steps taken to address the display of FIG. 6 to display red.

FIGs. 8A-8D depict the steps taken to address the display of FIG. 6 to display blue.

FIGs. 9A-9C depict the steps taken to address the display of FIG. 6 to display green.

FIG. 10 is a perspective embodiment of a rear electrode structure for addressing a seven segment display.

5 FIG. 11 is a perspective embodiment of a rear electrode structure for addressing a three by three matrix display element.

FIG. 12 is a cross-sectional view of a printed circuit board used as a rear electrode addressing structure.

10 FIG. 13 is a cross-sectional view of a dielectric sheet used as a rear electrode addressing structure.

FIG. 14 is a cross-sectional view of a rear electrode addressing structure that is formed by printing.

FIG. 15 is a perspective view of an embodiment of a control grid addressing structure.

15 FIG. 16 is an embodiment of an electrophoretic display that can be addressed using a stylus.

Detailed Description of the Invention

An electronic ink is an optoelectronically active material which comprises at least two phases: an electrophoretic contrast media phase and a coating/binding phase. The
20 electrophoretic phase comprises, in some embodiments, a single species of electrophoretic particles dispersed in a clear or dyed medium, or more than one species of electrophoretic particles having distinct physical and electrical characteristics dispersed in a clear or dyed medium. In some embodiments the electrophoretic phase is encapsulated, that is, there is a capsule wall phase between the two phases. The coating/binding phase
25 includes, in one embodiment, a polymer matrix that surrounds the electrophoretic phase. In this embodiment, the polymer in the polymeric binder is capable of being dried, crosslinked, or otherwise cured as in traditional inks, and therefore a printing process can be used to deposit the electronic ink onto a substrate. An electronic ink is capable of

being printed by several different processes, depending on the mechanical properties of the specific ink employed. For example, the fragility or viscosity of a particular ink may result in a different process selection. A very viscous ink would not be well-suited to deposition by an inkjet printing process, while a fragile ink might not be used in a knife
5 over roll coating process.

The optical quality of an electronic ink is quite distinct from other electronic display materials. The most notable difference is that the electronic ink provides a high degree of both reflectance and contrast because it is pigment based (as are ordinary printing inks). The light scattered from the electronic ink comes from a very thin layer of
10 pigment close to the top of the viewing surface. In this respect it resembles an ordinary, printed image. Also, electronic ink is easily viewed from a wide range of viewing angles in the same manner as a printed page, and such ink approximates a Lambertian contrast curve more closely than any other electronic display material. Since electronic ink can be printed, it can be included on the same surface with any other printed material, including
15 traditional inks. Electronic ink can be made optically stable in all display configurations, that is, the ink can be set to a persistent optical state. Fabrication of a display by printing an electronic ink is particularly useful in low power applications because of this stability.

Electronic ink displays are novel in that they can be addressed by DC voltages and draw very little current. As such, the conductive leads and electrodes used to deliver the
20 voltage to electronic ink displays can be of relatively high resistivity. The ability to use resistive conductors substantially widens the number and type of materials that can be used as conductors in electronic ink displays. In particular, the use of costly vacuum-sputtered indium tin oxide (ITO) conductors, a standard material in liquid crystal devices, is not required. Aside from cost savings, the replacement of ITO with other materials can
25 provide benefits in appearance, processing capabilities (printed conductors), flexibility, and durability. Additionally, the printed electrodes are in contact only with a solid binder, not with a fluid layer (like liquid crystals). This means that some conductive materials, which would otherwise dissolve or be degraded by contact with liquid crystals,

can be used in an electronic ink application. These include opaque metallic inks for the rear electrode (e.g., silver and graphite inks), as well as conductive transparent inks for either substrate. These conductive coatings include semiconducting colloids, examples of which are indium tin oxide and antimony-doped tin oxide. Organic conductors

- 5 (polymeric conductors and molecular organic conductors) also may be used. Polymers include, but are not limited to, polyaniline and derivatives, polythiophene and derivatives, poly3,4-ethylenedioxythiophene (PEDOT) and derivatives, polypyrrole and derivatives, and polyphenylenevinylene (PPV) and derivatives. Organic molecular conductors include, but are not limited to, derivatives of naphthalene, phthalocyanine, and pentacene.
- 10 Polymer layers can be made thinner and more transparent than with traditional displays because conductivity requirements are not as stringent.

As an example, there are a class of materials called electroconductive powders which are also useful as coatable transparent conductors in electronic ink displays. One example is Zelec ECP electroconductive powders from DuPont Chemical Co. of

- 15 Wilmington, Delaware.

- Referring now to FIGs. 1A and 1B, an addressing scheme for controlling particle-based displays is shown in which electrodes are disposed on only one side of a display, allowing the display to be rear-addressed. Utilizing only one side of the display for electrodes simplifies fabrication of displays. For example, if the electrodes are disposed
- 20 on only the rear side of a display, both of the electrodes can be fabricated using opaque materials, because the electrodes do not need to be transparent.

- FIG. 1A depicts a single capsule 20 of an encapsulated display media. In brief overview, the embodiment depicted in FIG. 1A includes a capsule 20 containing at least one particle 50 dispersed in a suspending fluid 25. The capsule 20 is addressed by a first
- 25 electrode 30 and a second electrode 40. The first electrode 30 is smaller than the second electrode 40. The first electrode 30 and the second electrode 40 may be set to voltage potentials which affect the position of the particles 50 in the capsule 20.

The particles 50 represent 0.1% to 20% of the volume enclosed by the capsule 20. In some embodiments the particles 50 represent 2.5% to 17.5% of the volume enclosed by capsule 20. In preferred embodiments, the particles 50 represent 5% to 15% of the volume enclosed by the capsule 20. In more preferred embodiments the particles 50
5 represent 9% to 11% of the volume defined by the capsule 20. In general, the volume percentage of the capsule 20 that the particles 50 represent should be selected so that the particles 50 expose most of the second, larger electrode 40 when positioned over the first, smaller electrode 30. As described in detail below, the particles 50 may be colored any one of a number of colors. The particles 50 may be either positively charged or
10 negatively charged.

The particles 50 are dispersed in a dispersing fluid 25. The dispersing fluid 25 should have a low dielectric constant. The fluid 25 may be clear, or substantially clear, so that the fluid 25 does not inhibit viewing the particles 50 and the electrodes 30, 40 from position 10. In other embodiments, the fluid 25 is dyed. In some embodiments the
15 dispersing fluid 25 has a specific gravity matched to the density of the particles 50. These embodiments can provide a bistable display media, because the particles 50 do not tend to move in certain compositions absent an electric field applied via the electrodes 30, 40.

The electrodes 30, 40 should be sized and positioned appropriately so that
20 together they address the entire capsule 20. There may be exactly one pair of electrodes 30, 40 per capsule 20, multiple pairs of electrodes 30, 40 per capsule 20, or a single pair of electrodes 30, 40 may span multiple capsules 20. In the embodiment shown in FIGs. 1A and 1B, the capsule 20 has a flattened, rectangular shape. In these embodiments, the electrodes 30, 40 should address most, or all, of the flattened surface area adjacent the
25 electrodes 30, 40. The smaller electrode 30 is at most one-half the size of the larger electrode 40. In preferred embodiments the smaller electrode is one-quarter the size of the larger electrode 40; in more preferred embodiments the smaller electrode 30 is one-eighth the size of the larger electrode 40. In even more preferred embodiments, the

862220-2934760

smaller electrode 30 is one-sixteenth the size of the larger electrode 40. It should be noted that reference to "smaller" in connection with the electrode 30 means that the electrode 30 addresses a smaller amount of the surface area of the capsule 20, not necessarily that the electrode 30 is physically smaller than the larger electrode 40. For example, multiple capsules 20 may be positioned such that less of each capsule 20 is addressed by the "smaller" electrode 30, even though both electrodes 30, 40 are equal in size. It should also be noted that, as shown in FIG. 1C, electrode 30 may address only a small corner of a rectangular capsule 20 (shown in phantom view in FIG. 1C), requiring the larger electrode 40 to surround the smaller electrode 30 on two sides in order to properly address the capsule 20. Selection of the percentage volume of the particles 50 and the electrodes 30, 40 in this manner allow the encapsulated display media to be addressed as described below.

Electrodes may be fabricated from any material capable of conducting electricity so that electrode 30, 40 may apply an electric field to the capsule 20. As noted above, the rear-addressed embodiments depicted in FIGs. 1A and 1B allow the electrodes 30, 40 to be fabricated from opaque materials such as solder paste, copper, copper-clad polyimide, graphite inks, silver inks and other metal-containing conductive inks. Alternatively, electrodes may be fabricated using transparent materials such as indium tin oxide and conductive polymers such as polyaniline or polythiopenes. Electrodes 30, 40 may be provided with contrasting optical properties. In some embodiments, one of the electrodes has an optical property complementary to optical properties of the particles 50.

In one embodiment, the capsule 20 contains positively charged black particles 50, and a substantially clear suspending fluid 25. The first, smaller electrode 30 is colored black, and is smaller than the second electrode 40, which is colored white or is highly reflective. When the smaller, black electrode 30 is placed at a negative voltage potential relative to larger, white electrode 40, the positively-charged particles 50 migrate to the smaller, black electrode 30. The effect to a viewer of the capsule 20 located at position 10 is a mixture of the larger, white electrode 40 and the smaller, black electrode 30,

creating an effect which is largely white. Referring to FIG. 1B, when the smaller, black electrode 30 is placed at a positive voltage potential relative to the larger, white electrode 40, particles 50 migrate to the larger, white electrode 40 and the viewer is presented a mixture of the black particles 50 covering the larger, white electrode 40 and the smaller, black electrode 30, creating an effect which is largely black. In this manner the capsule 20 may be addressed to display either a white visual state or a black visual state.

Other two-color schemes are easily provided by varying the color of the smaller electrode 30 and the particles 50 or by varying the color of the larger electrode 40. For example, varying the color of the larger electrode 40 allows fabrication of a rear-addressed, two-color display having black as one of the colors. Alternatively, varying the color of the smaller electrode 30 and the particles 50 allow a rear-addressed two-color system to be fabricated having white as one of the colors. Further, it is contemplated that the particles 50 and the smaller electrode 30 can be different colors. In these embodiments, a two-color display may be fabricated having a second color that is different from the color of the smaller electrode 30 and the particles 50. For example, a rear-addressed, orange-white display may be fabricated by providing blue particles 50, a red, smaller electrode 30, and a white (or highly reflective) larger electrode 40. In general, the optical properties of the electrodes 30, 40 and the particles 50 can be independently selected to provide desired display characteristics. In some embodiments the optical properties of the dispersing fluid 25 may also be varied, e.g. the fluid 25 may be dyed.

In other embodiments the larger electrode 40 may be reflective instead of white. In these embodiments, when the particles 50 are moved to the smaller electrode 30, light reflects off the reflective surface 60 associated with the larger electrode 40 and the capsule 20 appears light in color, e.g. white (see FIG. 2A). When the particles 50 are moved to the larger electrode 40, the reflecting surface 60 is obscured and the capsule 20 appears dark (see FIG. 2B) because light is absorbed by the particles 50 before reaching the reflecting surface 60. The reflecting surface 60 for the larger electrode 40 may

possess retroflective properties, specular reflection properties, diffuse reflective properties or gain reflection properties. In certain embodiments, the reflective surface 60 reflects light with a Lambertian distribution. The surface 60 may be provided as a plurality of glass spheres disposed on the electrode 40, a diffractive reflecting layer such as a holographically formed reflector, a surface patterned to totally internally reflect incident light, a brightness-enhancing film, a diffuse reflecting layer, an embossed plastic or metal film, or any other known reflecting surface. The reflecting surface 60 may be provided as a separate layer laminated onto the larger electrode 40 or the reflecting surface 60 may be provided as a unitary part of the larger electrode 40. In the embodiments depicted by FIGs. 2C and 2D, the reflecting surface may be disposed below the electrodes 30, 40 vis-à-vis the viewpoint 10. In these embodiments, electrode 30 should be transparent so that light may be reflected by surface 60. In other embodiments, proper switching of the particles may be accomplished with a combination of alternating-current (AC) and direct-current (DC) electric fields and described below in connection with FIGs. 3A-3D.

In still other embodiments, the rear-addressed display previously discussed can be configured to transition between largely transmissive and largely opaque modes of operation (referred to hereafter as "shutter mode"). Referring back to FIGs. 1A and 1B, in these embodiments the capsule 20 contains at least one positively-charged particle 50 dispersed in a substantially clear dispersing fluid 25. The larger electrode 40 is transparent and the smaller electrode 30 is opaque. When the smaller, opaque electrode 30 is placed at a negative voltage potential relative to the larger, transmissive electrode 40, the particles 50 migrate to the smaller, opaque electrode 30. The effect to a viewer of the capsule 20 located at position 10 is a mixture of the larger, transparent electrode 40 and the smaller, opaque electrode 30, creating an effect which is largely transparent. Referring to FIG. 1B, when the smaller, opaque electrode 30 is placed at a positive voltage potential relative to the larger, transparent electrode 40, particles 50 migrate to the second electrode 40 and the viewer is presented a mixture of the opaque particles 50

covering the larger, transparent electrode 40 and the smaller, opaque electrode 30, creating an effect which is largely opaque. In this manner, a display formed using the capsules depicted in FIGs. 1A and 1B may be switched between transmissive and opaque modes. Such a display can be used to construct a window that can be rendered opaque.

5 Although FIGs. 1A-2D depict a pair of electrodes associated with each capsule 20, it should be understood that each pair of electrodes may be associated with more than one capsule 20.

A similar technique may be used in connection with the embodiment of FIGs. 3A, 3B, 3C, and 3D. Referring to FIG. 3A, a capsule 20 contains at least one dark or black
10 particle 50 dispersed in a substantially clear dispersing fluid 25. A smaller, opaque electrode 30 and a larger, transparent electrode 40 apply both direct-current (DC) electric fields and alternating-current (AC) fields to the capsule 20. A DC field can be applied to the capsule 20 to cause the particles 50 to migrate towards the smaller electrode 30. For example, if the particles 50 are positively charged, the smaller electrode is placed a
15 voltage that is more negative than the larger electrode 40. Although FIGs. 3A-3D depict only one capsule per electrode pair, multiple capsules may be addressed using the same electrode pair.

The smaller electrode 30 is at most one-half the size of the larger electrode 40. In preferred embodiments the smaller electrode is one-quarter the size of the larger electrode
20 40; in more preferred embodiments the smaller electrode 30 is one-eighth the size of the larger electrode 40. In even more preferred embodiments, the smaller electrode 30 is one-sixteenth the size of the larger electrode 40.

Causing the particles 50 to migrate to the smaller electrode 30, as depicted in FIG. 3A, allows incident light to pass through the larger, transparent electrode 40 and be
25 reflected by a reflecting surface 60. In shutter mode, the reflecting surface 60 is replaced by a translucent layer, a transparent layer, or a layer is not provided at all, and incident light is allowed to pass through the capsule 20, i.e. the capsule 20 is transmissive.

Referring now to FIG. 3B, the particles 50 are dispersed into the capsule 20 by applying an AC field to the capsule 20 via the electrodes 30, 40. The particles 50, dispersed into the capsule 20 by the AC field, block incident light from passing through the capsule 20, causing it to appear dark at the viewpoint 10. The embodiment depicted in FIGs. 3A-3B may be used in shutter mode by not providing the reflecting surface 60 and instead providing a translucent layer, a transparent layer, or no layer at all. In shutter mode, application of an AC electric field causes the capsule 20 to appear opaque. The transparency of a shutter mode display formed by the apparatus depicted in FIGs. 3A-3D may be controlled by the number of capsules addressed using DC fields and AC fields. For example, a display in which every other capsule 20 is addressed using an AC field would appear fifty percent transmissive.

FIGs. 3C and 3D depict an embodiment of the electrode structure described above in which electrodes 30, 40 are on "top" of the capsule 20, that is, the electrodes 30, 40 are between the viewpoint 10 and the capsule 20. In these embodiments, both electrodes 30, 40 should be transparent. Transparent polymers can be fabricated using conductive polymers, such as polyaniline, polythiophenes, or indium tin oxide. These materials may be made soluble so that electrodes can be fabricated using coating techniques such as spin coating, spray coating, meniscus coating, printing techniques, forward and reverse roll coating and the like. In these embodiments, light passes through the electrodes 30, 40 and is either absorbed by the particles 50, reflected by retroreflecting layer 60 (when provided), or transmitted throughout the capsule 20 (when retroreflecting layer 60 is not provided).

The addressing structure depicted in FIGs. 3A-3D may be used with electrophoretic display media and encapsulated electrophoretic display media. FIGs. 3A-3D depict embodiments in which electrode 30, 40 are statically attached to the display media. In certain embodiments, the particles 50 exhibit bistability, that is, they are substantially motionless in the absence of a electric field. In these embodiments, the electrodes 30, 40 may be provided as part of a "stylus" or other device which is scanned

over the material to address each capsule or cluster of capsules. This mode of addressing particle-based displays will be described in more detail below in connection with FIG. 16.

Referring now to FIGs. 4A and 4B, a capsule 20 of a electronically addressable media is illustrated in which the technique illustrated above is used with multiple rear-addressing electrodes. The capsule 20 contains at least one particle 50 dispersed in a clear suspending fluid 25. The capsule 20 is addressed by multiple smaller electrodes 30 and multiple larger electrodes 40. In these embodiments, the smaller electrodes 30 should be selected to collectively be at most one-half the size of the larger electrodes 40. In further embodiments, the smaller electrodes 30 are collectively one-fourth the size of the larger electrodes 40. In further embodiments the smaller electrodes 30 are collectively one-eighth the size of the larger electrodes 40. In preferred embodiments, the smaller electrodes 30 are collectively one-sixteenth the size of the larger electrodes. Each electrode 30 may be provided as separate electrodes that are controlled in parallel to control the display. For example, each separate electrode may be substantially simultaneously set to the same voltage as all other electrodes of that size. Alternatively, the electrodes 30, 40 may be interdigitated to provide the embodiment shown in FIGs. 4A and 4B.

Operation of the rear-addressing electrode structure depicted in FIGs. 4A and 4B is similar to that described above. For example, the capsule 20 may contain positively charged, black particles 50 dispersed in a substantially clear suspending fluid 25. The smaller electrodes 30 are colored black and the larger electrodes 40 are colored white or are highly reflective. Referring to FIG. 4A, the smaller electrodes 30 are placed at a negative potential relative to the larger electrodes 40, causing particles 50 migrate within the capsule to the smaller electrodes 30 and the capsule 20 appears to the viewpoint 10 as a mix of the larger, white electrodes 40 and the smaller, black electrodes 30, creating an effect which is largely white. Referring to Fig. 4B, when the smaller electrodes 30 are placed at a positive potential relative to the larger electrodes 40, particles 50 migrate to the larger electrodes 40 causing the capsule 20 to display a mix of the larger, white

electrodes 40 occluded by the black particles 50 and the smaller, black electrodes 30, creating an effect which is largely black. The techniques described above with respect to the embodiments depicted in FIGs. 1A and 1B for producing two-color displays work with equal effectiveness in connection with these embodiments.

5 FIGs. 5A and 5B depict an embodiment of a rear-addressing electrode structure that creates a reflective color display in a manner similar to halftoning or pointillism. The capsule 20 contains white particles 55 dispersed in a clear suspending fluid 25. Electrodes 42, 44, 46, 48 are colored cyan, magenta, yellow, and white respectively. Referring to FIG 5A, when the colored electrodes 42, 44, 46 are placed at a positive
10 potential relative to the white electrode 48, negatively-charged particles 55 migrate to these three electrodes, causing the capsule 20 to present to the viewpoint 10 a mix of the white particles 55 and the white electrode 48, creating an effect which is largely white. Referring to FIG. 5B, when electrodes 42, 44, 46 are placed at a negative potential relative to electrode 48, particles 55 migrate to the white electrode 48, and the eye 10 sees
15 a mix of the white particles 55, the cyan electrode 42, the magenta electrode 44, and the yellow electrode 46, creating an effect which is largely black or gray. By addressing the electrodes, any color can be produced that is possible with a subtractive color process. For example, to cause the capsule 20 to display an orange color to the viewpoint 10, the yellow electrode 46 and the magenta electrode 42 are set to a voltage potential that is
20 more positive than the voltage potential applied by the cyan electrode 42 and the white electrode 48. Further, the relative intensities of these colors can be controlled by the actual voltage potentials applied to the electrodes.

 In another embodiment, depicted in FIG. 6, a color display is provided by a capsule 20 of size d containing multiple species of particles in a clear, dispersing fluid 25.
25 Each species of particles has different optical properties and possess different electrophoretic mobilities (μ) from the other species. In the embodiment depicted in FIG. 6, the capsule 20 contains red particles 52, blue particles 54, and green particles 56, and

852280" 2384760

$$|\mu_R| > |\mu_B| > |\mu_G|$$

That is, the magnitude of the electrophoretic mobility of the red particles 52, on average, exceeds the electrophoretic mobility of the blue particles 54, on average, and the electrophoretic mobility of the blue particles 54, on average, exceeds the average electrophoretic mobility of the green particles 56. As an example, there may be a species of red particle with a zeta potential of 100 millivolts (mV), a blue particle with a zeta potential of 60 mV, and a green particle with a zeta potential of 20 mV. The capsule 20 is placed between two electrodes 32, 42 that apply an electric field to the capsule.

FIGs. 7A-7B depict the steps to be taken to address the display shown in FIG. 6 to display a red color to a viewpoint 10. Referring to FIG. 7A, all the particles 52, 54, 56 are attracted to one side of the capsule 20 by applying an electric field in one direction. The electric field should be applied to the capsule 20 long enough to attract even the more slowly moving green particles 56 to the electrode 34. Referring to FIG. 7B, the electric field is reversed just long enough to allow the red particles 52 to migrate towards the electrode 32. The blue particles 54 and green particles 56 will also move in the reversed electric field, but they will not move as fast as the red particles 52 and thus will be obscured by the red particles 52. The amount of time for which the applied electric field must be reversed can be determined from the relative electrophoretic mobilities of the particles, the strength of the applied electric field, and the size of the capsule.

FIGs. 8A-8D depict addressing the display element to a blue state. As shown in FIG. 8A, the particles 52, 54, 56 are initially randomly dispersed in the capsule 20. All the particles 52, 54, 56 are attracted to one side of the capsule 20 by applying an electric field in one direction (shown in FIG. 8B). Referring to FIG. 8C, the electric field is reversed just long enough to allow the red particles 52 and blue particles 54 to migrate towards the electrode 32. The amount of time for which the applied electric field must be reversed can be determined from the relative electrophoretic mobilities of the particles,

the strength of the applied electric field, and the size of the capsule. Referring to FIG. 8D, the electric field is then reversed a second time and the red particles 52, moving faster than the blue particles 54, leave the blue particles 54 exposed to the viewpoint 10.

The amount of time for which the applied electric field must be reversed can be
5 determined from the relative electrophoretic mobilities of the particles, the strength of the applied electric field, and the size of the capsule.

FIGs. 9A-9C depict the steps to be taken to present a green display to the viewpoint 10. As shown in FIG. 9A, the particles 52, 54, 56 are initially distributed randomly in the capsule 20. All the particles 52, 54, 56 are attracted to the side of the
10 capsule 20 proximal the viewpoint 10 by applying an electric field in one direction. The electric field should be applied to the capsule 20 long enough to attract even the more slowly moving green particles 56 to the electrode 32. As shown in FIG. 9C, the electric field is reversed just long enough to allow the red particles 52 and the blue particles 54 to migrate towards the electrode 54, leaving the slowly-moving green particles 56 displayed
15 to the viewpoint. The amount of time for which the applied electric field must be reversed can be determined from the relative electrophoretic mobilities of the particles, the strength of the applied electric field, and the size of the capsule.

In other embodiments, the capsule contains multiple species of particles and a dyed dispersing fluid that acts as one of the colors. In still other embodiments, more than
20 three species of particles may be provided having additional colors. Although FIGS. 6-9C depict two electrodes associated with a single capsule, the electrodes may address multiple capsules or less than a full capsule

In FIG. 10, the rear substrate 100 for a seven segment display is shown that improves on normal rear electrode structures by providing a means for arbitrarily
25 connecting to any electrode section on the rear of the display without the need for conductive trace lines on the surface of the patterned substrate or a patterned counter electrode on the front of the display. Small conductive vias through the substrate allow connections to the rear electrode structure. On the back of the substrate, these vias are

connected to a network of conductors. These conductors can be run so as to provide a simple connection to the entire display. For example, segment 112 is connected by via 114 through the substrate 116 to conductor 118. A network of conductors may run multiple connections (not shown) to edge connector 122. This connector can be built into the structure of the conductor such as edge connector 122. Each segment of the rear electrode can be individually addressed easily through edge connector 122. A continuous top electrode can be used with the substrate 116.

The rear electrode structure depicted in FIG. 10 is useful for any display media, but is particularly advantageous for particle-based displays because such displays do not have a defined appearance when not addressed. The rear electrode should be completely covered in an electrically conducting material with room only to provide necessary insulation of the various electrodes. This is so that the connections on the rear of the display can be routed without concern for affecting the appearance of the display. Having a mostly continuous rear electrode pattern assures that the display material is shielded from the rear electrode wire routing.

In FIG. 11, a 3x3 matrix is shown. Here, matrix segment 124 on a first side of substrate 116 is connected by via 114 to conductor 118 on a second side of substrate 116. The conductors 118 run to an edge and terminate in an edge connector 122. Although the display element of FIG. 11 shows square segments 124, the segments may be shaped or sized to form a predefined display pattern.

In FIG. 12, a printed circuit board 138 is used as the rear electrode structure. The front of the printed circuit board 138 has copper pads 132 etched in the desired shape. There are plated vias 114 connecting these electrode pads to an etched wire structure 136 on the rear of the printed circuit board 138. The wires 136 can be run to one side or the rear of the printed circuit board 138 and a connection can be made using a standard connector such as a surface mount connector or using a flex connector and anisotropic glue (not shown). Vias may be filled with a conductive substance, such as solder or conductive epoxy, or an insulating substance, such as epoxy.

Alternatively, a flex circuit such a copper-clad polyimide may be used for the rear electrode structure of FIG. 10. Printed circuit board 138 may be made of polyimide, which acts both as the flex connector and as the substrate for the electrode structure. Rather than copper pads 132, electrodes (not shown) may be etched into the copper covering the polyimide printed circuit board 138. The plated through vias 114 connect the electrodes etched onto the substrate the rear of the printed circuit board 138, which may have an etched conductor network thereon (the etched conductor network is similar to the etched wire structure 136).

In FIG. 12, a thin dielectric sheet 150, such as polyester, polyimide, or glass can be used to make a rear electrode structure. Holes 152 are punched, drilled, abraded, or melted through the sheet where conductive paths are desired. The front electrode 154 is made of conductive ink printed using any technique described above. The holes should be sized and the ink should be selected to have a viscosity so that the ink fills the holes. When the back structure 156 is printed, again using conductive ink, the holes are again filled. By this method, the connection between the front and back of the substrate is made automatically.

In FIG. 14, the rear electrode structure can be made entirely of printed layers. A conductive layer 166 can be printed onto the back of a display comprised of a clear, front electrode 168 and a printable display material 170. A clear electrode may be fabricated from indium tin oxide or conductive polymers such as polyanilines and polythiophenes. A dielectric coating 176 can be printed leaving areas for vias. Then, the back layer of conductive ink 178 can be printed. If necessary, an additional layer of conductive ink can be used before the final ink structure is printed to fill in the holes.

This technique for printing displays can be used to build the rear electrode structure on a display or to construct two separate layers that are laminated together to form the display. For example an electronically active ink may be printed on an indium tin oxide electrode. Separately, a rear electrode structure as described above can be

printed on a suitable substrate, such as plastic, polymer films, or glass. The electrode structure and the display element can be laminated to form a display.

Referring now to FIG. 15, a threshold may be introduced into an electrophoretic display cell by the introduction of a third electrode. One side of the cell is a continuous, transparent electrode 200 (anode). On the other side of the cell, the transparent electrode is patterned into a set of isolated column electrode strips 210. An insulator 212 covers the column electrodes 210, and an electrode layer on top of the insulator is divided into a set of isolated row electrode strips 230, which are oriented orthogonal to the column electrodes 210. The row electrodes 230 are patterned into a dense array of holes, or a grid, beneath which the exposed insulator 212 has been removed, forming a multiplicity of physical and potential wells.

A positively charged particle 50 is loaded into the potential wells by applying a positive potential (e.g. 30V) to all the column electrodes 210 while keeping the row electrodes 230 at a less positive potential (e.g. 15V) and the anode 200 at zero volts. The particle 50 may be a conformable capsule that situates itself into the physical wells of the control grid. The control grid itself may have a rectangular cross-section, or the grid structure may be triangular in profile. It can also be a different shape which encourages the microcapsules to situate in the grid, for example, hemispherical.

The anode 200 is then reset to a positive potential (e.g. 50V). The particle will remain in the potential wells due to the potential difference in the potential wells: this is called the Hold condition. To address a display element the potential on the column electrode associated with that element is reduced, e.g. by a factor of two, and the potential on the row electrode associated with that element is made equal to or greater than the potential on the column electrode. The particles in this element will then be transported by the electric field due to the positive voltage on the anode 200. The potential difference between row and column electrodes for the remaining display elements is now less than half of that in the normal Hold condition. The geometry of the potential well structure and voltage levels are chosen such that this also constitutes a Hold condition, i.e., no

particles will leave these other display elements and hence there will be no half-select problems. This addressing method can select and write any desired element in a matrix without affecting the pigment in any other display element. A control electrode device can be operated such that the anode electrode side of the cell is viewed.

5 The control grid may be manufactured through any of the processes known in the art, or by several novel processes described herein. That is, according to traditional practices, the control grid may be constructed with one or more steps of photolithography and subsequent etching, or the control grid may be fabricated with a mask and a “sandblasting” technique.

10 In another embodiment, the control grid is fabricated by an embossing technique on a plastic substrate. The grid electrodes may be deposited by vacuum deposition or sputtering, either before or after the embossing step. In another embodiment, the electrodes are printed onto the grid structure after it is formed, the electrodes consisting of some kind of printable conductive material which need not be clear (e.g. a metal or
15 carbon-doped polymer, an intrinsically conducting polymer, etc.).

 In a preferred embodiment, the control grid is fabricated with a series of printing steps. The grid structure is built up in a series of one or more printed layers after the cathode has been deposited, and the grid electrode is printed onto the grid structure. There may be additional insulator on top of the grid electrode, and there may be multiple
20 grid electrodes separated by insulator in the grid structure. The grid electrode may not occupy the entire width of the grid structure, and may only occupy a central region of the structure, in order to stay within reproducible tolerances. In another embodiment, the control grid is fabricated by photoetching away a glass, such as a photostructural glass.

 In an encapsulated electrophoretic image display, an electrophoretic suspension,
25 such as the ones described previously, is placed inside discrete compartments that are dispersed in a polymer matrix. This resulting material is highly susceptible to an electric field across the thickness of the film. Such a field is normally applied using electrodes attached to either side of the material. However, as described above in connection with

862280" 23304760

FIGs. 3A-3D, some display media may be addressed by writing electrostatic charge onto one side of the display material. The other side normally has a clear or opaque electrode. For example, a sheet of encapsulated electrophoretic display media can be addressed with a head providing DC voltages.

- 5 In another implementation, the encapsulated electrophoretic suspension can be printed onto an area of a conductive material such as a printed silver or graphite ink, aluminized mylar, or any other conductive surface. This surface which constitutes one electrode of the display can be set at ground or high voltage. An electrostatic head consisting of many electrodes can be passed over the capsules to addressing them.
- 10 Alternatively, a stylus can be used to address the encapsulated electrophoretic suspension.

- In another implementation, an electrostatic write head is passed over the surface of the material. This allows very high resolution addressing. Since encapsulated electrophoretic material can be placed on plastic, it is flexible. This allows the material to be passed through normal paper handling equipment. Such a system works much like a
- 15 photocopier, but with no consumables. The sheet of display material passes through the machine and an electrostatic or electrophotographic head addresses the sheet of material.

- In another implementation, electrical charge is built up on the surface of the encapsulated display material or on a dielectric sheet through frictional or triboelectric charging. The charge can built up using an electrode that is later removed. In another
- 20 implementation, charge is built up on the surface of the encapsulated display by using a sheet of piezoelectric material.

- FIG. 16 shows an electrostatically written display. Stylus 300 is connected to a positive or negative voltage. The head of the stylus 300 can be insulated to protect the user. Dielectric layer 302 can be, for example, a dielectric coating or a film of polymer.
- 25 In other embodiments, dielectric layer 302 is not provided and the stylus 300 contacts the encapsulated electrophoretic display 304 directly. Substrate 306 is coated with a clear conductive coating such as ITO coated polyester. The conductive coating is connected to ground. The display 304 may be viewed from either side.

Microencapsulated displays offer a useful means of creating electronic displays, many of which can be coated or printed. There are many versions of microencapsulated displays, including microencapsulated electrophoretic displays. These displays can be made to be highly reflective, bistable, and low power.

5 To obtain high resolution displays, it is useful to use some external addressing means with the microencapsulated material. This invention describes useful combinations of addressing means with microencapsulated electrophoretic materials in order to obtain high resolution displays.

10 One method of addressing liquid crystal displays is the use of silicon-based thin film transistors to form an addressing backplane for the liquid crystal. For liquid crystal displays, these thin film transistors are typically deposited on glass, and are typically made from amorphous silicon or polysilicon. Other electronic circuits (such as drive electronics or logic) are sometimes integrated into the periphery of the display. An emerging field is the deposition of amorphous or polysilicon devices onto flexible
15 substrates such as metal foils or plastic films.

 The addressing electronic backplane could incorporate diodes as the nonlinear element, rather than transistors. Diode-based active matrix arrays have been demonstrated as being compatible with liquid crystal displays to form high resolution devices.

20 There are also examples of crystalline silicon transistors being used on glass substrates. Crystalline silicon possesses very high mobilities, and thus can be used to make high performance devices. Presently, the most straightforward way of constructing crystalline silicon devices is on a silicon wafer. For use in many types of liquid crystal displays, the crystalline silicon circuit is constructed on a silicon wafer, and then transferred to a glass substrate by a "liftoff" process. Alternatively, the silicon transistors
25 can be formed on a silicon wafer, removed via a liftoff process, and then deposited on a flexible substrate such as plastic, metal foil, or paper. As another implementation, the silicon could be formed on a different substrate that is able to tolerate high temperatures (such as glass or metal foils), lifted off, and transferred to a flexible substrate. As yet

another implementation, the silicon transistors are formed on a silicon wafer, which is then used in whole or in part as one of the substrates for the display.

The use of silicon-based circuits with liquid crystals is the basis of a large industry. Nevertheless, these display possess serious drawbacks. Liquid crystal displays are inefficient with light, so that most liquid crystal displays require some sort of backlighting. Reflective liquid crystal displays can be constructed, but are typically very dim, due to the presence of polarizers. Most liquid crystal devices require precise spacing of the cell gap, so that they are not very compatible with flexible substrates. Most liquid crystal displays require a "rubbing" process to align the liquid crystals, which is both difficult to control and has the potential for damaging the TFT array.

The combination of these thin film transistors with microencapsulated electrophoretic displays should be even more advantageous than with liquid crystal displays. Thin film transistor arrays similar to those used with liquid crystals could also be used with the microencapsulated display medium. As noted above, liquid crystal arrays typically requires a "rubbing" process to align the liquid crystals, which can cause either mechanical or static electrical damage to the transistor array. No such rubbing is needed for microencapsulated displays, improving yields and simplifying the construction process.

Microencapsulated electrophoretic displays can be highly reflective. This provides an advantage in high-resolution displays, as a backlight is not required for good visibility. Also, a high-resolution display can be built on opaque substrates, which opens up a range of new materials for the deposition of thin film transistor arrays.

Moreover, the encapsulated electrophoretic display is highly compatible with flexible substrates. This enables high-resolution TFT displays in which the transistors are deposited on flexible substrates like flexible glass, plastics, or metal foils. The flexible substrate used with any type of thin film transistor or other nonlinear element need not be a single sheet of glass, plastic, metal foil, though. Instead, it could be constructed of

paper. Alternatively, it could be constructed of a woven material. Alternatively, it could be a composite or layered combination of these materials.

As in liquid crystal displays, external logic or drive circuitry can be built on the same substrate as the thin film transistor switches.

5 In another implementation, the addressing electronic backplane could incorporate diodes as the nonlinear element, rather than transistors.

In another implementation, it is possible to form transistors on a silicon wafer, dice the transistors, and place them in a large area array to form a large, TFT-addressed display medium. One example of this concept is to form mechanical impressions in the receiving substrate, and then cover the substrate with a slurry or other form of the transistors. With agitation, the transistors will fall into the impressions, where they can be bonded and incorporated into the device circuitry. The receiving substrate could be glass, plastic, or other nonconductive material. In this way, the economy of creating transistors using standard processing methods can be used to create large-area displays without the need for large area silicon processing equipment.

10

15

While the examples described here are listed using encapsulated electrophoretic displays, there are other particle-based display media which should also work as well, including encapsulated suspended particles and rotating ball displays.

While the invention has been particularly shown and described with reference to specific preferred embodiments, it should be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

20

352280 290460

CLAIMS

What is claimed is:

- 1 1. An electrophoretic display comprising:
2 at least one capsule containing a suspending fluid and at least a first particle and a
3 second particle, said first particle having a first optical property and a first electrophoretic
4 mobility and said second particle having a second optical property and a second
5 electrophoretic mobility; and
6 at least two electrodes disposed adjacent said capsule;
7 wherein application of an electric field to said capsule by said electrodes causes
8 said capsule to change visual state responsive to the optical properties and electrophoretic
9 mobilities of said particles.
- 1 2. The electrophoretic display of claim 1 wherein said first electrophoretic mobility
2 and said second electrophoretic mobility are substantially non-overlapping.
- 1 3. The electrophoretic display of claim 1 wherein said capsule contains at least one
2 red particle, at least one blue particle, and at least one green particle.
- 1 4. The electrophoretic display of claim 1 wherein said suspending fluid is
2 substantially transparent.
- 1 5. The electrophoretic display of claim 1 wherein said suspending fluid is dyed.
- 1 6. An electrophoretic display comprising:
2 at least one capsule containing a suspending fluid and at least one particle;
3 at least two electrodes disposed adjacent the capsule,
4 wherein application of a voltage potential to one of said at least two
5 electrodes causes said at least one particle to migrate within said capsule, causing said
6 capsule to change its visual state.

802000 23504100

1 7. The electrophoretic display of claim 6 wherein said suspending fluid is
2 substantially transparent.

1 8. The electrophoretic display of claim 6 wherein said at least one particle has an
2 optical property matching an optical property of one of said at least two electrodes.

1 9. The electrophoretic display of claim 6 wherein said at least one particle is
2 substantially white.

10. An electrophoretic display comprising:
at least one capsule containing a suspending fluid and at least one particle;
a cyan-colored electrode disposed adjacent said capsule;
a magenta-colored electrode disposed adjacent said capsule, said magenta-colored electrode spaced apart from said cyan-colored electrode;
a yellow-colored electrode disposed adjacent said capsule, said yellow-colored electrode spaced apart from said cyan-colored electrode and said magenta-colored electrode; and
a white electrode adjacent said capsule, said white electrode spaced apart from said cyan-colored electrode, said yellow-colored electrode, and said magenta-colored electrode;
wherein application of a voltage potential to said cyan-colored electrode, magenta-colored electrode, and yellow-colored electrode causes said white particles to migrate within the capsule to locations adjacent said cyan-colored electrode, said magenta-colored electrode, and said yellow-colored electrode causing said capsule to appear white, and wherein application of a second voltage potential to said cyan-colored, said magenta-colored, and said yellow-colored electrode causes said white particles to migrate within said capsule to a location adjacent said white electrode causing said capsule to appear substantially black.

COLOR ELECTROPHORETIC DISPLAYS

Abstract of the Disclosure

Novel addressing schemes for controlling electronically addressable displays include a scheme for rear-addressing displays, which allows for in-plane switching of the display material. Other schemes include a rear-addressing scheme which uses a retroreflecting surface to enable greater viewing angle and contrast. Another scheme
5 includes an electrode structure that facilitates manufacture and control of a color display. Another electrode structure facilitates addressing a display using an electrostatic stylus. Methods of using the disclosed electrode structures are also disclosed. Another scheme includes devices combining display materials with silicon transistor addressing structures.

412JDL2108/2.644897-1

364,238,000-238,041,600

862280 29804460




FIG. 1A




FIG. 1B




FIG. 1C

86/280" 29804460




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A

FIG. 3B




FIG. 3C

FIG. 3D

00140562.002790




FIG. 4A




FIG. 4B

862230-2220760




FIG. 5A














FIG. 5B

86/280" 29804760





20250429 20250429






FIG. 10







FIG. 11.



862280-2980460

20250428



3542207 29804760




FIG 15





FIG. 16

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

1. Application papers are not suitable for scanning and are not in compliance with 37 CFR 1.52 because:
 - ☐ All sheets must be the same size and either A4 (21 cm x 29.7 cm) or 8-1/2" x 11". Pages _____ do not meet these requirements.
 - ☐ Papers are not flexible, strong, smooth, non-shiny, durable, and white.
 - ☐ Papers are not typewritten or mechanically printed in permanent ink on one side.
 - ☐ Papers contain improper margins. Each sheet must have a left margin of at least 2.5 cm (1") and top, bottom and right margins of at least 2.0 cm (3/4").
 - ☐ Papers contain hand lettering.
2. Drawings are not in compliance and were not scanned because:
 - ☐ The drawings or copy of drawings are not suitable for electronic reproduction.
 - ☐ All drawings sheets are not the same size. Pages must be either A4 (21 cm x 29.7 cm) or 8-1/2" x 11".
 - ☐ Each sheet must include a top and left margin of at least 2.5 cm (1"), a right margin of at least 1.5 cm (9/16") and a bottom margin of at least 1.0 cm (3/8").
3. Page(s) _____ are not of sufficient clarity, contrast and quality for electronic reproduction.
4. Page(s) _____ are missing.
5. OTHER: NO Declaration